

PRODUCT SPECIFICATIONS

7006B

Description

Tradesman+, Standard harness, Non-belted.

The Tradesman+ full body harness introduces greater levels of comfort, fit, durability and functionality to the user.

The new tri-layer air mesh shoulder yoke and enhanced webbing on FallTech's TRADESMAN+ harnesses deliver greater comfort and durability.

Sizes

- **PN 7006B** -- UniFit
- **PN 7006BX/2X** -- Dual Size XL/XXL

Features

- Three D-rings, Back and Side; Mating Buckle Legs and QC Chest and 10" Shoulder Pads
- One Back D-ring; QC Buckle Legs and Chest
- Quick Connect Visi-lock chest buckle
- Low-profile spring-tension Torso Adjusters
- Two side D-Rings

Material Specifications

Webbing:	Polyester; Min. 5,000 lbs. tensile strength
Keepers:	Plastic
D-Ring:	Alloy Steel; Min. 5,000 lbs. tensile strength
Buckles/Adjusters:	Alloy Steel; Min. 3,375 lbs. tensile strength
Shoulder Strap Grab Handle:	Vinyl
Shoulder Adjusters:	Friction
Leg Buckles:	Mating
Foam:	Open cell

Performance Specifications

Maximum Working Load:	425 lbs
ANSI User Capacity:	130 to 310 lbs Max.
OSHA User Capacity:	130 to 425 lbs Max.

Relevant Standards

OSHA:	CFR1926.502, CFR1910.66
ANSI:	Z359.11-14

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.



FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THIS INFORMATION HOWEVER, IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.