

PRODUCT SPECIFICATIONS

7008BHVD

Tradesman+ Hi-Vis Standard Non-belted Full Body Harness

Tradesman+ High-Visibility harnesses incorporate nearly 20 years of end-user acceptance, productivity and manufacturing proficiency as the standard of day-in day-out performance and reliability. Serviceable functionality and trusted quality are built upon with added user benefits to last all day and every day without imposing a premium expense.

- High-Visibility Orange web with linear reflective thread striping
- Exclusive dorsal SRL attachment sleeve
- Tri-layer padded air-mesh shoulder yoke
- Traditional low-profile spring-tension torso adjusters
- Paired lanyard parking keepers
- Tongue Buckle legs with Mating Buckle chest



Available Sizes	
7008BHVDXS	Extra Small
7008BHVD	UniFit (S,M,L)
7008BHVDX/2X	XL/2X
7008BHVD3X	3X

Materials Specifications	
Webbing	Polyester, 5,000 lbs. Min. Static Strength
D-rings	Plated Alloy Steel; 5,000 lbs. Min. Static Strength
Buckle/ Adjusters	Plated Alloy Steel; 3,375 lbs. Min. Static Strength

Performance Specifications	
Static Strength	3,600 lbs. Minimum
ANSI User Capacity	310 lbs. Max
OSHA User Capacity	425 lbs. Max

Relevant Standards	
ANSI	Z359.14-2014
OSHA	1926.502, 1910.66