

PRODUCT SPECIFICATIONS

7078BSM, 7078BLX, 7078B2X Tradesman Plus Construction Belted Harnesses

Tradesman Plus harness incorporate nearly 20 years of end-user acceptance for performance and reliability. Serviceable functionality and trusted quality are enhanced with added features while not imposing a premium expense. Integrated dorsal SRL sleeve, Visi-lock Quick-Connect chest buckles, Tri-layer padded shoulder yoke, reinforced waist pad, and low-profile spring-tension torso adjusters are all standard on Tradesman Plus harnesses.

- Exclusive dorsal SRL attachment sleeve provides simple use of twin-leg personal SRLs.
- Tri-layer padded air-mesh shoulder yoke and reinforced waist support and positioning pad.
- Alloy steel dorsal and hip D-rings for Fall Arrest and Work Positioning applications.
- Visi-lock quick connect chest buckle and tongue buckle leg closures with 9 adjustment positions.
- Low-profile spring-tension torso adjusters and paired lanyard parking keepers.
- Available in dual and single sizes small to 2X.



ANSI Performance Specifications

Static Strength	3,600 lbs. Min.
ANSI User Capacity	310 lbs. Max
OSHA User Capacity	425 lbs. Max

Available Part #s

7078BSM	Dual-size Small/Med
7078BLX	Dual-size Large/XL
7078B2X	2XL

Materials Specifications

Webbing	Polyester, 5,000 lbs. Min. Static Strength
D-rings	Plated Alloy Steel, 5,000 lbs. Min. Static Strength
Buckles/Adjusters	Plated Alloy Steel, 3,375 lbs. Min. Static Strength

Relevant Standards

ANSI	Z359.11-2014
OSHA	1926.502 and 1910.66