

PRODUCT SPECIFICATIONS

7226CLE, 7227CLE, 7232CLE, 7268CLE, 7265CLE DuraTech® Leading Edge Self-Retracting Lifelines


FallTech™ DuraTech® Leading Edge SRLs feature a dual deceleration system including an internal inertial brake and external energy absorber to reduce the risk of cable failure when contacting a sharp leading edge during a fall event. DuraTech® LE SRLs may be anchored overhead and up to 5' below the dorsal D-ring. All DuraTech® LE SRLs are thoroughly tested to and meet the rigorous ANSI Z359.14-2014 LE standard specifically for leading edge performance.

Performance Specifications					
Part #	7226CLE	7227CLE	7232CLE	7265CLE	7268CLE
ANSI SRL Class	A	B	B	B	B
Average Arrest Force	1,575 lbs. Max	1,125 lbs. Max			
Maximum Arrest Distance	24" or Less	54" or Less			
Static Strength	3,000 lbs. Minimum				
User Capacity	130 - 310 lbs. Maximum				
Maximum Arrest Force	1800 lbs.				

Materials Specifications		
Cable	7/32" 7x1 Galvanized Steel	3,400 lbs. Min. Static Strength
Connector	Load-Indicating Swivel Snap Hook	5,000 lbs. Min. Static Strength
Housing and Drum	Aluminum Alloy	

Relevant Standards	
ANSI	Z359.14-2014 LE
OSHA	1926.502, 1910.66

Part #	Cable Length	Weight	Housing Dimensions		
			A Length	B Width	C Thickness
7226CLE	15'	14 lbs.	9½"	6¾"	3¾"
7227CLE	20'	16.4 lbs.	11"	8"	4"
7232CLE	30'	17.5 lbs.	11"	8"	4"
7268CLE	50'	25 lbs.	12¾"	9¾"	4½"
7265CLE	60'	28 lbs.	12¾"	9¾"	4½"



PRICING

50' DuraTech® Leading Edge SRL

Part #	Description	Pack Qty.	Weight Each	List Price
7268CLE	50'DuraTech® Leading Edge SRL	1	25 lbs.	\$797

