

PRODUCT SPECIFICATIONS

72706TH5 DuraTech 6' Mini Web Self-Retracting Device with SRD Connector

- Twin-leg SRD for 100% tie-off
- 6' working length
- Compact and impact resistant nylon housing
- Integral shock absorber provides visual fall event indication
- Integral Swivel eye - Reduces twisting
- Aluminum Rebar Hooks on leg ends
- Triple-lock Dorsal SRD Connector enjoins Swivel-eyes

MATERIALS SPECIFICATIONS	
Webbing:	100% Dyneema
Energy Absorber:	Polyester
Swivel Eye:	Alloy Steel, 5/8" hole diameter
Spring:	Rolled Carbon Steel
SRD Housing:	Nylon 6/6
Main Shaft:	Alloy Steel
Pawls:	Stainless Steel
Connectors	Aluminum Alloy, 5,000 Min. Static Strength; 3,600 lbs. Gate Strength

PERFORMANCE SPECIFICATIONS	
Tensile Strength:	Min. 3,000 lbs. Tensile Strength
Max. Capacity:	310 lbs.
Max. Arrest Distance:	54"
Average Arrest Force:	Less than 900 lbs.
Max. Arrest Force:	1,800 lbs.
Class of SRD:	Class B

RELEVANT STANDARDS	
ANSI	Z359.14-2014
OSHA	1926.502, 1910.66



72706TH5

WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Remove from service if there is any sign of activation.

Warning: All Fall Protection equipment should only be used after reading and understanding the manufacturer's instructions and proper training on the product. Failure to receive proper training and follow the manufacturer's instructions could result in serious injury or death.