

PRODUCT SPECIFICATIONS

Arc Flash 6' Shock Absorbing Lanyard

#8242AF

Features

- Single-leg lanyard for fall arrest.
- SoftPack shock absorber is designed to limit arrest forces to an average of 900 lbs.
- Nomex cover protects shock absorber from damage due to exposure to excessive heat.
- 1-1/4" Kevlar webbing has a tensile strength of 10,000 lbs.
- Double-locking snap hooks at the attachment and anchorage ends.

Material Specifications

Webbing:	<i>Kevlar; Min. 10,000 lbs. tensile strength</i>
Energy Absorber:	<i>Polyester; activation greater than 450 lbs.</i>
Connectors:	<i>Alloy Steel; Min. 5,000 lbs. tensile strength</i>
Connector Gates:	<i>Alloy Steel; Min. 3,600 lbs. front and side load</i>

Performance Specifications

Tensile Strength:	<i>Min. 5,000 lbs.</i>
Max. Capacity:	<i>310 lbs.</i>
Max. Freefall:	<i>6 feet</i>
Average Arrest Force:	<i>Less than 900 lbs.</i>
Max. Elongation:	<i>48 inches</i>

Relevant Standards

OSHA:	<i>CFR1926.502, CFR1910.66</i>
ANSI:	<i>Z359.13-2009</i>

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Remove from service if there is any signs of activation.
- Never attach a Shock Absorbing Lanyard to the front or side D-rings.



*Image shown is 7242

FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.