

PRODUCT SPECIFICATIONS

WeldTech 6' Shock Absorbing Lanyard

#8242Y3

Features

- Y-leg lanyard for 100% tie-off.
- SoftPack shock absorber
- Nomex cover protects shock absorber from damage due to exposure to heat and welding slag
- 1-1/2" Kevlar webbing lanyard legs
- 1 Snap Hook and 2 Rebar Hooks

Material Specifications

Webbing: Kevlar; Min. 10,000 lbs. tensile strength
Energy Absorber: Polyester; activation greater than 450 lbs.
Connectors: Alloy Steel; Min. 5,000 lbs. tensile strength
Connector Gates: Alloy Steel; Min. 3,600 lbs. front and side load

Performance Specifications

Tensile Strength: Min. 5,000 lbs.
Max. Capacity: 310 lbs.
Max. Freefall: 6 feet
Average Arrest Force: Less than 900 lbs.
Max. Elongation: 48 inches

Relevant Standards

OSHA: CFR1926.502, CFR1910.66
ANSI: Z359.13-2009

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Remove from service if there is any signs of activation.
- Never attach a Shock Absorbing Lanyard to the front or side D-rings.



FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.