

# PRODUCT SPECIFICATIONS

## 8256PC Coated Energy Absorbing Lanyard

### Features

- Patented ViewPack absorber cover with inspection window
- Urethane coating on lanyard leg protects against oil, paint and solvents
- Includes vinyl coated absorber cover for easy clean-up

### MATERIALS SPECIFICATIONS

<b>Webbing:</b>	Coated Polyester; 5,000 lbs. Min. static strength
<b>Connectors:</b>	Alloy Steel; 5,000 lbs. Min. with 3,600 lbs. gates

### ANSI PERFORMANCE SPECIFICATIONS

<b>Static Strength:</b>	5,000 lbs. Min.
<b>ANSI Lanyard Class :</b>	6 ft Free Fall
<b>Max. Arrest Distance :</b>	48"
<b>Average Arrest Force :</b>	900 lbs.
<b>Max. Arrest Force :</b>	1,800 lbs.
<b>ANSI User Capacity:</b>	310 lbs. Max.
<b>OSHA User Capacity:</b>	310 lbs. Max.

### RELEVANT STANDARDS

<b>ANSI:</b>	Z359.13-2013
<b>OSHA:</b>	1926.502 and 1910.66



### WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Never connect an Energy Absorbing Lanyard to Hip D-ring.

**Warning:** All Fall Protection equipment should only be used after reading and understanding the manufacturer's instructions and proper training on the product. Failure to receive proper training and follow the manufacturer's instructions could result in serious injury or death.