

PRODUCT SPECIFICATIONS

ViewPack 6' Shock Absorbing Lanyard

#826073A

Features

- "Y"-leg lanyard for 100% tie off.
- Anchorage end rebar hooks have a 2 - 1/4" gate opening and allow a broader range of connections.
- ViewPack shock absorber is designed to limit arrest forces to 900 lbs. or less

Material Specifications

Webbing:	<i>Polyester; Min. 5,000 lbs. tensile strength</i>
Energy Absorber:	<i>Polyester</i>
Connectors:	<i>Alluminum alloy steel; Min. 5,000 lbs. tensile strength</i>
Connector Gates:	<i>Alloy Steel; Min. 3,600 lbs. front and side load</i>

Performance Specifications

Tensile Strength:	<i>Min. 5,000 lbs.</i>
ANSI Max. Capacity:	<i>310 lbs. max</i>
ANSI Class:	<i>6' free fall</i>
Max. Arrest Distance:	<i>48"</i>
Average Arrest Force:	<i>900 lbs.</i>
Max. Arrest Force:	<i>1,800 lbs.</i>
Min. Activation Force:	<i>450 lbs.</i>

Relevant Standards

OSHA:	<i>CFR1926.502, CFR1910.66</i>
ANSI:	<i>Z359.13-2013</i>

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Remove from service if there are any signs of activation.
- Never attach a Shock Absorbing Lanyard to the front or side D-rings.



FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.